



Technical data sheet

FORGED EYE BOLTS (DERIVED FROM DIN 580:2018) WITH UNC-8UN THREAD



MATERIALS

- C15E + Al
- INOX - AISI304
- INOX - AISI316

FINISHES

- Electro-galvanized zinc plating
- Hot dip galvanizing

CERTIFICATES

- EN10204 3.1
- EN10204 2.2



Body	Ø D1	Threads per inch	Ø D2	Ø D3	Ø D4	E	F	H	K	L1	L2	M	Weight	WLL ¹	WLL ²	WLL ³	WLL ⁴
	mm	Nr	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	kg	kg	kg	kg
8	1/4	20	20	36	20	6	2,5	36	8	13	49	10	0,06	100	70	50	50
8	5/16	18	20	36	20	6	2,5	36	8	13	49	10	0,06	140	100	70	70
10	3/8	16	25	45	25	8	3	45	10	17	62	12	0,11	230	170	115	115
10	7/16	14	25	45	25	8	3	45	10	17	62	12	0,11	230	170	115	115
12	7/16	14	30	54	30	10	3,5	53	12	20,5	73,5	14	0,18	230	170	115	115
12	1/2	13	30	54	30	10	3,5	53	12	20,5	73,5	14	0,18	340	240	170	170
16	9/16	12	35	63	35	12	4	62	14	27	89	16	0,28	490	350	245	245
16	5/8	11	35	63	35	12	4	62	14	27	89	16	0,28	700	500	350	350
20	3/4	10	40	72	40	14	5	71	16	30	101	19	0,45	1200	860	600	600
20	7/8	9	40	72	40	14	5	71	16	30	101	19	0,45	1200	860	600	600
24	7/8	9	50	90	50	18	6	90	20	36	126	24	0,74	1400	1000	700	700
24	1"	8	50	90	50	18	6	90	20	36	126	24	0,74	1800	1290	900	900
30	1 1/8	7	65	108	60	22	7	109	24	45	154	28	1,66	3200	2300	1600	1600
30	1 1/4	7	65	108	60	22	7	109	24	45	154	28	1,66	3200	2300	1600	1600

Technical data sheet

FORGED EYE BOLTS (DERIVED FROM DIN 580:2018) WITH UNC-8UN THREAD

Body	Ø D1	Threads per inch	Ø D2	Ø D3	Ø D4	E	F	H	K	L1	L2	M	Weight ~	WLL ¹	WLL ²	WLL ³	WLL ⁴
	mm	Nr	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	kg	kg	kg	kg
36	1"1/4	7	75	126	70	26	8	128	28	54	182	32	2,65	3200	2300	1600	1600
36	1"3/8	6	75	126	70	26	8	128	28	54	182	32	2,65	4600	3300	2300	2300
42	1"1/2	6	85	144	80	30	9	147	32	63	210	38	4,03	4600	3300	2300	2300
42	1"5/8	6	85	144	80	30	9	147	32	63	210	38	4,03	6300	4500	3150	3150
48	1"3/4	5	100	166	90	35	10	168	38	68	236	46	6,38	6300	4500	3150	3150
48	2"	4,5	100	166	90	35	10	168	38	68	236	46	6,38	8600	6100	4300	4300
56	2"1/4	4,5	110	184	100	38	11	187	42	78	265	50	8,80	11500	8200	5750	5750
64	2"1/2	4	120	206	110	42	12	208	48	90	298	58	12,40	16000	11000	8000	8000
72	2"3/4	4	150	260	140	50	12	260	60	100	360	72	23,30	20000	14000	10000	10000
72	3"	4	150	260	140	50	12	260	60	100	360	72	23,30	20000	14000	10000	10000
80	3"1/4	4	170	296	160	55	12	298	68	112	410	80	34,20	28000	20000	14000	14000
100	3"1/2	4	190	330	180	60	12	330	75	130	460	88	49,10	28000	20000	14000	14000
100	3"3/4	4	190	330	180	60	12	330	75	130	460	88	49,10	28000	20000	14000	14000
100	4"	4	190	330	180	60	12	330	75	130	460	88	49,10	40000	29000	20000	20000

Dimension variations available on request

SOME WARNINGS FOR THE CORRECT USE OF EYE BOLTS
Always read the complete instructions before use



The eyebolts must always be screwed until their support plane adheres to the surface of the piece to be lifted.
Do not use the eyebolts if they cannot be screwed in fully.



Do not use eyebolts with lateral ring pull



Do not use eyebolts with lateral ring pull